

Product data sheet

Thistle® ProTape FT100

Thistle ProTape FT100 is a wide self-adhesive glass fibre mesh tape.

Where to use

Use it to reinforce flat joints in skim finishes to plasterboard backgrounds and for placing over gaps and reinforcement to small areas of damaged plasterboard.



Product information

Composition

This product is a self adhesive glass fibre mesh tape.

Colour

White.

Lengths available (m)

45.

Width (mm)

100.

Installation guidance

Limitations of use

Please note that Thistle ProTape is not a direct substitute for Gyproc Joint Tape. Where there is an increased risk of cracking, or where joints exceed 3mm, the joints are to be reinforced with Gyproc Joint Tape bedded in Thistle plaster.

Cutting

Cut the product to size using a knife, scraper or trowel.

Application

Plastering to board backgrounds

Flat plasterboard joints can be reinforced with Thistle ProTape glass fibre mesh tape. Position the tape and spread the plaster along each joint. To minimise the risk of cracking, ensure that the plaster is pushed through the tape well into any gaps in between the plasterboards. Apply plaster to the plasterboard surface and joints with firm pressure after the joint treatment has stiffened but not set. Build out to a 2mm thickness in two applications, wet-on-wet and trowel to a smooth matt finish.

Jointing

When using Thistle ProTape, bedding is not required, but the filling material should be pressed through the holes in the Thistle ProTape, particularly if there is a gap between the plasterboard joints. This is important to achieve a satisfactory appearance to the finished joint.

Trowel apply two or three applications of jointing compound, allowing each to set or dry before the next application, feathering each out beyond the previous application. Make an equal number of applications to screw/nail spots. Sand each joint application as required to achieve a smooth surface.

Product data sheet

Thistle® ProTape FT100



Sitework

Packaging overview

45m roll in cardboard carton, 12 rolls per carton.

Quantity per carton	12 rolls
---------------------	----------

Storage

Store in a dry place between 5°C and 25°C, keep out of sunlight and protect from frost.

Environmental

Recyclability

This product cannot be recycled.

Disposal

Waste should be disposed of in accordance with local authority requirements.



"Gyproc", "Thistle", "ThistlePro", "Gypframe" and "Glasroc" are all registered trademarks of Saint-Gobain Construction Products UK Limited. "Isover" is a registered trademark of Saint-Gobain Isover (French legal entity) and "Okarno" is a registered trademark of Okarno Limited.

Saint-Gobain Construction Products UK Limited is a limited company registered in England under company number 734396, having its registered office at Saint-Gobain House, East Leake, Loughborough, Leicestershire, LE12 6JU, UK. Saint-Gobain Construction Products UK Limited trades as British Gypsum for part of its business activities.

British Gypsum reserves the right to revise product specification without notice. The information herein should not be read in isolation as it is meant only as guidance for the user, who should always ensure that they are fully conversant with the products and systems being used and their subsequent installation prior to the commencement of work. For a comprehensive and up-to-date library of information visit the British Gypsum website at: british-gypsum.com. For information about products supplied by Artex Limited or Saint-Gobain Isover please see their respective websites.

"British Gypsum" is a registered trademark of Saint-Gobain Construction Products UK Limited.